

@ www.alpoverseas.com

First time in India EPDM Accoflooring



- Wide range application
- UV and ozone resistant
- Anti-fungal & anti-bacterial
- Non-toxic
- Non-polar
- Non-corrosive
- Biodegradable
- Recyclable
- Long Life

A versatile product which in addition to its beautiful aesthetics, also works as acoustics insulation, sports & gym flooring, and Noise Dampening. ALP EPDM Accouflooring come with properties such as excellent UV & Ozone resistance and excellent durability. This flooring is fully recyclable and biodegradable and can be used across multiple applications.

THICKNESS 2, 3, 4, 5, 7 & 10 mm

ROLL SIZE 10, 15 & 20 mtrs.

MATERIAL EPDM

DESIGNMultiple sparkle colors

Description

- Suitable for all floor finishes including ceramic, granite, stone and marble tiles.
- Offers long term performance without collapse or "bottoming" out under high points loads.
- Resistant to ageing and deformation
- Quick and easy to install. Simply bond to the sub-floor beneath the final floor finish.
- Zero global warming potential (GWP) & zero ozone depletion potential (ODP)
- Independent test data available for both site and field tests to show compliance with both approved document E & Section H of the building regulations.
- Accreditation to ISO 9001, ISO 14001 and ISO 18001

Technical Information

Density (ASTM D 1056)	900 - 1200 Kg/m³
Tensile Strength (ASTM D412)	Min 10 Kgf/cm ²
Elongation at Break (ASTM D 412)	Min 50%
Application Temperature	-40°C to +120°C
Burning Rate	FMVSS 302 (Pass)
Burning Rate	IS 15061 (Pass)
STC (DIN:52210 Part IV-1984)	DIN: 52210 Part IV-1984
Thermal Conductivity (ASTM C 518)	0.049 W/m.K @20°C
Adhesive Type (For Self Adhesive)	Acrylic-PSA

Applications

EPDM acoustic underlay is widely used in developments where effective sound control is essential and interior design flexibility is a priority.


These include: **Sports | Apartments | Education** Developments | Hotels | Commercial Developments | Leisure Developments | Architectural Projects

Sound proofing acoustic underlay is suitable for under resilient, vinyl floors, linoleum, rubber floors, epoxy floors and a variety of other hard floor finishes.

Another important application of soundproofing acoustic underlay is under T&G timber, plywood, CFC sheeting, carpet, heavy duty screed beds as well as customised acoustic systems.

INSTALLATION


Precast Floor




minimum 300kg/m2

OVERSEAS

In-situ Concrete Slab Floor



Beam & Block Floor





ALP OVERSEAS PVT. LTD.

Corporate Office: Plot No. 32, Sector-18 HUDA, Gurgaon, Haryana - 122015 (INDIA)

Telephone: +91-124-4731500 | **Website**: www.alpoverseas.com







